

Product datasheet

Specifications



Switch, Unica X, 1 way, 16AX, 250V, 1 gang, stainless steel

NUX31_1_SS

Main

Range of product	Unica X
Product or component type	Switch
Device presentation	Complete product
Technology type	Electromechanical
Switch function	1-way
Number of rocker	1
Device application	Light control
Colour tint	Stainless steel

Complementary

Rated current	16 AX
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Condition of use	Indoor use
Opening distance	> 3 mm
Actuator	Rocker
Connections - terminals	Screw terminal
Material	Stainless steel
Surface finish	Matt
specific treatment - integrated within the material	Metallic
Device mounting	Flush
Width	86 mm
Height	86 mm
Depth	27 mm
Embedding depth	19 mm
Ambient air temperature for operation	-5...45 °C
Ambient air temperature for storage	-5...60 °C
Standards	IEC 60669-1
Product certifications	IEC

Excluding VAT, FCA Jabal Ali & amp; are subject to change – check with your local distributor.

Environment

IP degree of protection IP20

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 2.65 cm

Package 1 Width 8.6 cm

Package 1 Length 8.6 cm

Package 1 Weight 181.5 g

Unit Type of Package 2 BB1

Number of Units in Package 2 10

Package 2 Height 9.5 cm

Package 2 Width 19 cm

Package 2 Length 19.5 cm

Package 2 Weight 1.919 kg

Unit Type of Package 3 CAR

Number of Units in Package 3 60

Package 3 Height 21 cm

Package 3 Width 30 cm

Package 3 Length 40 cm

Package 3 Weight 12.111 kg

Contractual warranty

Warranty (in months) 18



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	2 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.1 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.4 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	77
End of life manual availability	No need of specific recycling operations
Take-back	Nej

Image of product / Alternate images

Alternative









Image of product in real life situation

